

8924-CT3022-LE

High Rendering, Dynamic Warm White



24 2350K • 95+ CRI

2650K • 95+ CRI

30 2950K • 95+ CRI





90+ CRI

UL Class 2

IP20 Dry Location

Custom Cut to Fit

50,000 Hour Min. Lifespan

Requires: Aion LED Driver, Approved Controller, AT, WT or ST Series Housing. Sold Separately, Not Included

Tested as suitable for use within clothing closet spaces by ETL/ Intertek

Must be installed in accordance with NEC 410.16 for use in clothing closet spaces









instructional materials for more information. Authorized installers only. Systems tested prior to shipping.









8924-CT3022-LE

Standard Output Dynamic White Light Engine





2 Channel Fixture:

CH 1: 3000K ~2.8W/ft. CH 2: 2150K ~2.8W/ft.

Max. Increment:

(Dictated by Programming)

Max 48W per Channel

Min. Increment:

2 in.

0.555" O	
0.10"	

	@2150K	@2950K
Total Lumens	126.64	206.60
Input Power	2.26 W	2.82 W
Efficacy	56.80	79
Color Rendering Index	94+ CRI	92+ CRI
R9	71.30	68.06
Input Voltage (VDC)	24.00	24.00
Input Current (Amp)	0.09	0.11
Correlated Color Temperature	2150K	2950K















REQUIRES D100-X2 DRIVER, DMX CONTROLLER AND 800-SERIES HOUSING Sold Separately, Not Included